


TECHNICAL DATASHEET

EGGER LAMINATE FLOORING


Coreboard		HDF swell stopp plus
Profil		The patented EGGER installation system <i>JUST clic!</i> stands for quick and simple installation process without glue. Patented as <i>JUST clic!</i> EP 1 441 087 and EP 1 462 587
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use	32	
European Norm		
Format	Classic	
Dimension mm (length x width)	1292 x 192	
Complete thickness	8	
Thickness of silenizio® special cellulose		
Bevel	-	
	Packaging	
Pallet	One-way-pallet	
Paket information		
	Piece	8
	m2	1,98
	kg	14,43
Pallet information		
	Piece	480
	m2	119,07
	kg	866,00
Classification and general requirements		
abrasion resistance according EN13329	AC4 (IP ≥ 4000)	
impact resistance according EN13329	IC2	
resistance to staining EN438	group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425	No change in appearance or damage	
Castor chairs according EN12529	Type W	
Thickness swelling according EN13329	≤ 18 %	
tolerance of top layer according EN13329	length ± 0,2 mm width ± 0,1 mm thickness ± 0,3 mm	
Light fastness according EN13329	blue wool scale ≥ level 6 grey wool scale ≥ level 4	
Static indentation by constant pressure according EN13329	< 0,01	
Thermal resistance according to EN 12667	0,06 m² K/W	



TECHNICAL DATASHEET

EGGER LAMINATE FLOORING

Coreboard		HDF swell stopp plus
Profil		The patented EGGER installation system <i>JUST clic!</i> stands for quick and simple installation process without glue. Patented as <i>JUST clic!</i> EP 1 441 087 and EP 1 462 587
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use	33	
European Norm		
Format	Classic	
Dimension mm (length x width)	1292 x 192	
Complete thickness	8	
Thickness of silenzio® special cellulose		
Bevel	-	
	Packaging	
Pallet	One-way-pallet	
Paket information		
	Piece	8
	m2	1,98
	kg	14,43
Pallet information		
	Piece	480
	m2	119,07
	kg	866,00
Classification and general requirements		
abrasion resistance according EN13329	AC5 (IP ≥ 6000)	
impact resistance according EN13329	IC3	
resistance to staining EN438	group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425	No change in appearance or damage	
Castor chairs according EN12529	Type W	
Thickness swelling according EN13329	≤ 18 %	
tolerance of top layer according EN13329	length ± 0,2 mm width ± 0,1 mm thickness ± 0,3 mm	
Light fastness according EN13329	blue wool scale ≥ level 6 grey wool scale ≥ level 4	
Static indentation by constant pressure according EN13329	< 0,01	
Thermal resistance according to EN 12667	0,06 m² K/W	



TECHNICAL DATASHEET

EGGER LAMINATE FLOORING

Coreboard		HDF swell stopp plus
Profil		The patented UNI <i>fit!</i> installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use	32	
European Norm		
Format	Large	
Dimension mm (length x width)	1291 x 246	
Complete thickness	8	
Thickness of silenizio® special cellulose		
Bevel	WV4	
Pallet	Packaging	
Paket information	One-way-pallet	
	Piece	8
	m2	2,54
	kg	18,00
Pallet information		
	Piece	360
	m2	114,30
	kg	822,00
Classification and general requirements		
abrasion resistance according EN13329	AC4 (IP ≥ 4000)	
impact resistance according EN13329	IC2	
resistance to staining EN438	group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425	No change in appearance or damage	
Castor chairs according EN12529	Type W	
Thickness swelling according EN13329	≤ 18 %	
tolerance of top layer according EN13329	length ± 0,2 mm width ± 0,1 mm thickness ± 0,3 mm	
Light fastness according EN13329	blue wool scale ≥ level 6 grey wool scale ≥ level 4	
Static indentation by constant pressure according EN13329	< 0,01	
Thermal resistance according to EN 12667	0,06 m² K/W	



TECHNICAL DATASHEET

EGGER LAMINATE FLOORING

Coreboard		HDF swell stopp plus
Profil		The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use		33
European Norm		
Format		CLASSIC
Dimension mm (length x width)		1291 x 193
Complete thickness		11
Thickness of silenzio® special cellulose		
Bevel		WV4
Pallet		Packaging One-way-pallet
Paket information		
	Piece	6
	m2	1,49
	kg	14,90
Pallet information		
	Piece	312
	m2	77,74
	kg	775,00
Classification and general requirements		
abrasion resistance according EN13329		AC5 (IP ≥ 6000)
impact resistance according EN13329		IC3
resistance to staining EN438		group 1 + 2: level 5 group 3: level 4
Effect of furniture leg according EN424		No damage shall be visible, when tested with foot Type 0 artefact
Effect of a castor chair according EN425		No change in appearance or damage
Castor chairs according EN12529		Type W
Thickness swelling according EN13329		≤ 18 %
tolerance of top layer according EN13329		length ± 0,2 mm width ± 0,1 mm thickness ± 0,3 mm
Light fastness according EN13329		blue wool scale ≥ level 6 grey wool scale ≥ level 4
Static indentation by constant pressure according EN13329		< 0,01
Thermal resistance according to EN 12667		0,12 m² K/W

